



20H PROBE

Magnetic Field Probe: B Field, DC ÷ 1000 Hz

Key Features:

- Frequency range: DC ÷ 1000 Hz
- Dynamic Range: > 80 dB
- Directivity: Isotropic
- Sensitivity > 1mT
- High pass filter (cut-off @ 1.5Hz)

Compatibility:

- NHT310 and NHT3D meters

Typical Application:

- MRI - Magnetic Resonance Imaging
- Galvanic treatments
- Railway power supply plants
- Metalworking processes



Information subject to change without prior notice

MICRⓂRAD

Distributed by:
Reliant EMC LLC
3311 Lewis Ave
Signal Hill CA 90755
408-916-5750
www.reliantemc.com



20H PROBE

Magnetic Field Probe: B Field, DC ÷ 1000 Hz

Description:

The 20H probe is based on a set of three mutually orthogonal Hall sensors. The three voltages, which correspond to the spatial components of the field, are available individually at the probe output. The NHT 310 or NHT 3D meter calculates the resulting isotropic field strength.

The probe detects magnetic fields from 0 to 1000 Hz. It is suitable for use in applications such as Magnetic Resonances Imaging (MRI), materials working plants (galvanic and mills) and power supply plants for railway stations.

Its high rate of 15 T makes it ideal for extremely strong magnetic field measurements such as those used for example in the latest generation or experimental magnetic resonance.

The presence of a first-order high-pass filter (20 dB / decade) with a 1.5Hz cutting frequency allows to discriminate the static component from the others at higher frequencies. In fact, the filter, when inserted, completely suppresses the continuous component and the probe band becomes 1.5 Hz ÷ 1000 Hz.

TECHNICAL SPECIFICATIONS	
Frequency range	0 ÷ 1000 Hz
Type of frequency response	Flat
Measurement range	1 mT ÷ 15 T
Dynamic range	80 dB
Sensor type	Hall sensors
Directivity	Isotropic
Frequency response	± 0.5 dB (0 Hz ÷ 1 kHz)
Linearity	± 0.5 dB (5 ÷ 2000 mT)
	± 1 dB (2 ÷ 15 T)
Isotropic response (@ 10mT)	± 0.5 dB (@ 10mT)
GENERAL CHARACTERISTICS	
Recommended calibration interval	24 months
Operation temperature	0°C ÷ 50°C
Size	300 x 16 Ø (mm)
Weight	63 g
Country of origin	Italy

Information subject to change without prior notice



Distributed by: Reliant EMC LLC, 3311 Lewis Ave., Signal Hill CA, 90755, 408-916-5750, www.reliantemc.com